

# VOIP PHONE SNOM 370

The Next Generation of VoIP Phones



- Tilttable high-definition graphical display (240x128 pixels)
- Call indication LED
- 47 keys, 13 LEDs
- 12 programmable function keys
- Speakerphone
- 2x IEEE 802.3 10/100 Mbps switch
- Power over Ethernet
- Multiple audio device support
- Expansion module with 42 programmable function keys
- SIP RFC3261
- Security: SIPS/SRTP, TLS
- STUN, ENUM, NAT, ICE
- Codecs: G.711, G.729A, G.723.1, G.722, G.726, GSM 6.10 (full rate)
- National Language Support

## → Usability

The snom 370 is the VoIP phone for the business user who needs immediate access to all of their important information.

With the large graphical, high-definition display, the snom 370 offers an improved and extended presentation of call lists, address books and caller information. Caller information can be customized easily through XML to depict the information the user wants displayed.

Through the mini browser, users can have direct access to their own applications via the display screen. Users can not only customize the design of the display but, also view news tickers and other information as well as access central or

## → Security

public phone directories. The large LED (red) announces incoming calls.

More flexibility and productivity for your everyday work life. The improved interface guarantees ease of use and comfort. Context-sensitive menus offer additional options according to individual requirements. The snom 370 supports several audio devices simultaneously, for example, it is possible to use the handset or headset and the loudspeaker concurrently.

More performance through expanded memory. The snom 370 offers more additional customer-oriented functionalities and applications. The expanded memory capacity enables the depiction

## → Interoperability

of graphics and high resolution pictures to show the status of contacts (e.g., busy, on-line, off-line) similar to Instant Messenger. It is also possible to play music and media files and to integrate applications like VPN for increased security.

Afraid of unwanted listeners, data theft or spam calls? To avoid problems with unwanted violations of your audio data, the snom 370 supports the security standards TLS (Transport Layer Security), SRTP, and SIPS which are necessary to protect against electronic eavesdropping and data theft.

# TECHNICAL DATA SNOM 370

## GENERAL FEATURES

- **Dimensions:**  
approx. 25x20x13.5 cm
- **Weight:** approx. 1000 g
- **Safety:** IEC 60950-1:2001,  
CB Test Certificate: DE 2-008417
- **Certifications:** FCC Class B,  
CE Mark
- **Power consumption:** 2.6–2.8 watts

## CONNECTORS

- **1 x LAN, 1 x PC:** RJ45 (Ethernet)
- **Power:** 5 V DC
- **Ethernet:** 2 x IEEE 802.3  
10/100 Mbps switch
- **Power over Ethernet:**  
IEEE 802.3af, Class 1
- **Handset:** RJ11 connector
- **Headset:** RJ11 connector
- **Expansion Module:**  
Proprietary snom connector

## USER INTERFACE

- 240x128 pixels, tiltable grayscale  
graphical display, backlight
- 47 keys, 12 programmable  
function keys with LEDs  
(54 with the expansion module)
- Call indication LED
- Caller-ID (with picture display)
- Message waiting indication LED
- Address book (250 entries)
- Address book import/export
- Speed dialing
- Local dial plan
- Number guessing
- Lists of missed, received and dialed  
calls (100 entries each)
- Call waiting indication
- Clock, daylight saving, call-timer
- Call blocking (deny list)
- Blocking of anonymous calls
- Handling of up to 12 calls  
simultaneously
- Menu-driven user interface
- Ring tone selection, import of  
individual ring tones
- URL Dialing support

- National language support for  
selected languages (NLS)
- Do not disturb
- Speakerphone (full duplex)
- Auto answer mode
- Keyboard lock

## CALL FEATURES

- Hold
- Blind transfer, attended transfer
- Music-on-hold support  
(only via PBX)
- Divert
- Conferencing (3-way conference  
bridge on phone)
- Call park, call pickup (only via PBX)
- Call completion
- Client Matter Code (CMC)
- Call waiting/switching between calls
- Redialing
- RTP multicast paging
- Multiple audio device support

## WEB SERVER

- Embedded web server HTTP/HTTPS
- Easy configuration of the phone,  
remote configuration
- Dial from web interface
- Password protection
- Diagnostics (tracing, logging, syslog)

## SECURITY, QUALITY OF SERVICE

- HTTPS (server/client)
- Transport Layer Security (TLS)
- SRTP (RFC3711), SIPS
- RTCP
- VLAN (802.1 pq)

## CODECS, AUDIO

- G.711 A-law,  $\mu$ -law
- G.729A, G.723.1, G.726
- GSM 6.10 (full rate)
- G.722
- Comfort noise,  
voice activity detection

## SIP

- RFC3261 compliance
- UDP, TCP and TLS
- Digest/basic authentication
- Loose routing and strict routing  
support
- PRACK (RFC3262)
- Error-information support
- Reliability of provisional responses  
(RFC3262)
- Early media support
- DNS SRV (RFC3263),  
redundant server support
- Offer/answer (RFC3264)
- Message Waiting Indication  
(RFC3842), subscription for  
MWI events (RFC3265)
- Dialog-state monitoring (RFC 4235)
- In-band DTMF/out-of-band DTMF/  
SIP INFO DTMF
- STUN client (NAT traversal)
- ENUM (RFC3261), NAPTR  
(RFC2915), rport (RFC3581),  
REFER (RFC3515)
- Event list subscription support  
(RFC4662)
- Bridged line appearance (BLA)
- Auto provisioning with PnP
- Presence/buddylist feature
- Busy lamp field support (BLF)
- Presence publishing

## INSTALLATION

- Automatic software update
- Automatic settings retrieval  
via HTTP/HTTPS/TFTP
- Installation via web interface
- Static IP provisioning, DHCP
- NTP

For more information, please contact your snom partner.

### snom technology AG

Gradestraße 46  
D-12347 Berlin  
tel/enum: +49 30 39833-0  
fax: +49 30 39833-111  
sip: info@snom.com  
mail: info@snom.com

Version 1.01/28 Feb 2007

Copyright © 2000–2007 snom technology AG. All rights reserved. snom is a registered trademark of snom technology AG and affiliates in Germany, USA and certain other countries and regions. Unless specified otherwise, all trademarks, in particular product names, in this document are legally protected trademarks of snom technology AG. Other trademarks or registered trademarks mentioned in this document are the property of their respective manufacturers or owners. Product specifications contained in this document are subject to change without notice.

[www.snom.com](http://www.snom.com)